



## 4DX Putty

### Product description

To be environment friendly Areva Paints have introduced Water based O2 Metallic Paint which when applied gives enormous sheen and protects the surface better because of its in built character , and also it has aluminium base. It has good opacity,coverage, drying fast, very good on metals, Good Scratch resistance.

### Recommended use

Primarily on Metals.

### Surface preparation

Ensure the metal surface to painted with O2 Metallic is free from dust, oil, Grease , Cracks etc., Apply coat of Red Oxide Metal Primer or Zinc Chrome yellow Primer and ensure the application of O2 Metallic Paint when the Primer has dried .

### Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable putty with mixture of sylo-1.

### Application method

By Brush , Roller or Spray .

### Thinning / Dilution

Portable Water 5-10% of water only .

### Drying Time

Touch Dry : 2 Hours  
Hard Dry : 8 Hours

### Coverage

180 Sq ft Per Litre Per Coat depending on the surface.

### Technical Detail

### Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs , 500 ML , 200 ML , 100 ML & 50ML .

### Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

### Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask. No added Lead, Mercury or chromium compounds .