

Gloss Putty

Product description

It is one of the finest Emulsion , Gloss Putty in the Industry. Because of carefully selected ingredients of raw material and finest , rich , emulsion resin the putty is very Smooth and Penetrates deep into Holes , Cracks , Crevices and makes the surface very even. Because of the Smoothness dust retention on the walls are very low , gives good opacity and Coverage.

Recommended use

For Interior of the walls where there is lot of Cracks, Holes, Crevices etc.,

Surface preparation

Ensure that the Surface to be painted it should be free from loose particles , dust, flakes, oil & grease etc., Address the proven and apply one coat of Areva Paints Water Based Cement Primer. After Primer has dried apply coat of Areva Paints Gloss Putty .

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1.

Application method

By Putty Blade or Spatula .

Thinning / Dilution

Direct

Drying Time

6 - 8 Hours

Coverage

Technical Detail

Shipping

Packing : 20 Kg , 10 Kg , 5 Kg , 1 Kg

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds