



Waterbase Florocoat

Product description

To go in line with our Country to avoid Pollution, introduced Water base Floorcoat Paint . This is a finish Paint, to apply the Paint it has to be thinned with water thereby avoiding Mineral Turpentine Oil.

Recommended use

For Cement Floor, concrete Floors, asbestos, metals, walls & wood but solely designed for floors .

Surface preparation

To follow procedure as laid down for surface preparation for Interior Walls , Exterior Walls , Wood & Metals . Floor area to be painted should be clean from Oil, Dust, grease, cracks, crevices etc., Ensure the surface is clean. It has good opacity and Coverage .

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable putty with mixture of sylo-1.

Application method

By Brush , Roller & Spray.
This Product comes in various vibrant colours also.

Thinning / Dilution

Portable Water 5-10% of water only .

Drying Time

TouchDry: 4-5 Hours
Hard Dry: 48 Hours

Coverage

180 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs , 500ML.

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool, dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggles & face mask. No added Lead, Mercury or chromium compounds .