



Product description

3D Putty Ultra is an acrylic emulsion based for the Interiors of the Wall. Because of its in build strength it gives a protective coating for the walls from fungal, moss, oil etc., It acts as a barrier and does not allow the Penetration of water . Has good Opacity , Coverage and good spread, environment friendly , no Health Hazards.

Recommended use

For Interior of the Walls .

Surface preparation

Ensure surface is free from Oil, dust, grease, fungal and moss attack, cracks & crevices. Apply a coat of Areva Paints water. Thinnable Cement Primer before application of Putty for Protection and longevity.

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1.

Application method

By Putty Blade, Knife or Spatula.

Thinning / Dilution

Direct

Drying Time

Touch Dry : 4-5 Hours
Hard Dry : 48 Hours

Coverage

Technical Detail

Shipping

Packing : 25 Kg , 20 Kg , 15 Kg , 10 Kg , 5 Kg , & 1 Kg.

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of ignition seek immediate medical attention. Wear eye Protection during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask. No added Lead, Mercury or chromium compounds .