



## Exterior Primer

### Product description

Unique Product which is Emulsion based for Exterior Walls take care of the direct sunlight, UV rays, Fungal attack, moss formation, because of the reflex action of the product it forms a barrier to the rains which will try to penetrate the walls and in built special chemicals gives a high protective coating, with good opacity and coverage.

### Recommended use

For all Exterior Walls.

### Surface preparation

Ensure the surface is free from oil, dust, Grease, flakes, fungal attack, moss growth, Cracks and crevices. Fill the cracks & crevices with Areva Paints Sylo-1 & Sylo-2 fillers. Apply one or two coats of Exterior Primer which takes care of the Protection of Walls.

### Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1.

### Application method

By brush or Spray.

### Thinning / Dilution

Potable water 10-20% of water only.

### Drying Time

Touch Dry : 1 Hour  
Hard Dry : 6 Hours

### Coverage

80-90 Sq ft Per Litre Per Coat depending on the surface.

### Technical Detail

### Shipping

Packing : 20Ltrs, 10Ltrs, 4Ltrs, 1 Ltrs

### Safety Features

Do not apply when there is a drop in temperature. Do not over-thin or over extend brush Stir well & strain before use.

### Precaution

Store the container with the lid tightly closed in an upright position in a cool, dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed. In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggles & face mask.. No added Lead, Mercury or chromium compounds