



Jointex Sealent

Product description

Jointex Sealent is one of the main ingredients when mixed with Jointex Powder in the ratio of 1:1 gives such protection to the surface that it is very tough to remove. It is polymer based material and penetrates into the holes, cracks and crevices and protects the surface with a hard coating .

Recommended use

Used on Churkey , Roof top, water tanks(non conventional),sajjas and on other surface which is exposed to heavy rains, sunlight , UV Rays etc.,

Surface preparation

Ensure the surface to be painted to be free from oil, grease , dust, cracks, crevices , loose flakes etc., treating the same ensure it is dry and a coat if Jointex Sealent and Jointex Powder mixed in the ratio of 1:1 and allow it to dry.

Pre-painting procedure

Application method

By Brush.

Thinning / Dilution

Direct mixing 1:1

Drying Time

Touch Dry : 1/2 an Hour
Hard Dry : 8 Hour

Coverage

35 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20 Kg , 10 Kg , 1 Kg & 1/2 Kg.

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds