

Nevo Primer

Product description	One of the best Emulsion based Cement Primer Water based Primer for all needs of Interior wall primer. Has good opacity, coverage, dries very fast . It is an Economy Primer suiting all segments .
Recommended use	For all Interior Walls .
Surface preparation	Ensure that the walls to be painted it should be free from loose particles , dust, flakes, Crevices , oil & grease etc., Ensure the surface is Clean, apply a coat of Nevo Primer, Putty , followed by Finish Paint .
Pre-painting procedure	The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1.
Application method	By Brush , Roller & Spray .
Thinning / Dilution	Portable Water 10-20% of water only .
Drying Time	<u>Touch Dry</u> : 1/2 an hour . Hard Dry : 5 Hours .
Coverage	90 Sq ft Per Litre Per Coat depending on the surface.
Technical Detail	
Shipping	Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs
Safety Features	Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.
Precaution	Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds