

## Roller Coat

### Product description

Roller coat is a specially designed product which is acrylic emulsion based paint to give designs on the walls . It is a very tough product and gives extended protection to the walls with added decorative values with varied designs and colours. very good opacity, Coverage , Flow, enhances beauty on the walls .

### Recommended use

Can be used for Internal as well as External walls under shade where direct sunlight is avoided .

### Surface preparation

Roller coat is applied on finished walls, hence dust , clean the surface free from oil, grease, cracks etc., and apply the paint.

### Pre-painting procedure

### Application method

By specially designed Rollers .

### Thinning / Dilution

### Drying Time

Touch Dry : 2 Hours  
Hard Dry : 8 Hours

### Coverage

5 Sq ft per kg per coat depending on the surface.

### Technical Detail

### Shipping

Packing : 20 Kg

### Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

### Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds