

Product description

Terrashield Plus is an Exterior acrylic emulsion based with special resins to take care the vagaries of nature like rain,sunlight , UV Rays etc.., It is Water thinnable Exterior finish paint with good opacity , coverage , faster drying with no health hazard for the applicator.

Recommended use

For all External walls of Buildings and Homes

Surface preparation

Ensure that the surface is free from Oil, dust, grease,cracks, crevices etc.., After necessary priming and putty with crack fillers apply 2 coats of Terrashield Plus.

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1. Apply a coat of idea petal exterior primer & allow it to dry before applying the top coats.

Application method

By Brush , Exterior Rollers & Spray .

Thinning / Dilution

Potable water 10-20% of water only.

Drying Time

Touch Dry : 1 Hour
Hard Dry : 6 Hour

Coverage

130 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail
Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds