



## Water Cut

### Product description

This Product is Elestromatic Water Proofing Compound in nature & designed solely for the purpose of Protection and to add aesthetic Values . This Product is stretchable it does not allow water to penetrate into the surface and also protects the previous coatings of Sylo-1 , Sylo-2 & Churkey Putty .

### Recommended use

Exterior walls roof & parapets Interior / Exterior.

### Surface preparation

Ensure that the surface is cleaned thoroughly with wire brush , remove all loose particles , dust, flakes , fungai, algae , moss grease, oil etc., care to be taken while brushing & see that the cement plastering on the walls are not damaged if the surface has dents, holes, cracks etc.,

### Pre-painting procedure

The surface is clean & dry if there are cracks or undulations fill it with suitable exterior putty with mixture of Sylo-1. Apply a coat of idea petal exterior primer & allow it to dry before applying the top coats.

### Application method

It can be brushed, rolled or sprayed. It is advisable for two coat system allowing a gap of 12 hours between coats.

### Thinning / Dilution

Potable water 10-20% of water only.

### Drying Time

Touch Dry : 1 Hour  
Hard Dry : 8 Hour

### Coverage

150 Sq ft Per Litre Per Coat depending on the surface.

### Technical Detail

### Shipping

Packing : 20Ltrs, 4Ltrs & 1 Ltrs .

### Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

### Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds